

RS232 Isolator

Part no.: AN232ISO



- Port-powered from RS232 port
- 3-wire protection (TX, RX and GND)
- Up to 1500V constant voltage protection
- 15KV ESD static protection
- Plug and play, no drivers required
- 2 year warranty
- CE, FCC, RoHS, ISO 9001 Compliant

If you need to effectively protect your RS232 ports and devices against high-voltage spikes, surges, ground-loops and other damaging voltages then this optical isolator is what you need. It effectively protects your RS232 devices for up to with 1500V constant voltage, 600W surge protection and 15KV ESD static protection.

The isolator is easy to connect, simply connect it with the DB9 connectors between your communication wire and your device. One isolator at each end of your communication wire is recommended if the communication distance is longer than 100 feet, however the recommended distance depends on the amount of static electricity in the surrounding environment. The port powered feature of this isolator means that you do not need to connect an external power supply to the unit, it gets its power from the RS232 port, it can do this effectively without interfering with the data communication.

This is a 3-wire isolator which means that it protects the TX, RX and GND communication wires. If you need to isolate all communication wires please see our 8-wire optical isolator.

NORDFIELD

Specialists in serial communication. With over 15 years of experience in the field we can solve most serial problems.

PRODUCTS

Large selection of Serial RS232, RS485 and RS422 converters, USB to Serial adapters, Isolators, Ethernet to Serial converters, Serial Repeaters, Wireless Serial modules, Serial Bluetooth adapters and Serial Port Cards.

TECHNICAL SUPPORT

To access technical support, please visit www.NordField.com where you will find:

- Latest drivers and updates
- Technical tips
- Documentation
- Configuration support
- and much more...
- Feel free to contact our technical
- support team at
- mail@usconverters.com

NordField

105 Stations West Drive Sedona, AZ 86336, USA www.NordField.com mail@NordField.com









Specifications

SPECIFICATIONS

of Eon to, thomas		
Model number	AN232ISO	
Lines protected	TXD, RXD, GND	
Baud rate	300 - 57,600bps	
Power	Port-powered -5VDC from RS232 port (TXD alternatively RTS, DTR)	
Current draw	Less than 15mA	
Interface PC side	DB9 female connector	
Optical isolation	1500V	
ESD protection	1500W / 600W/ms	
Working mode	Asynchronous, full transparent	
Standards	EIA/TIA RS-232C / RS232	
Operating Temp.	-40°C to 85°C	
Operating humidity	5% To 95% - No Condensation	
Dimensions	2.47" x 1.33" x 0.70" (62.8 mm x 33.8 mm x 17.8 mm)	
Warranty	2-year Limited Warranty	
ECCN	4A994.a	
Schedule B	8471.80.1000	
HTS	8517.18.0050	

NORDFIELD

Specialists in Serial Communication. With over 15 years of experience in the field we can solve most serial problems.

PRODUCTS

Large selection of Serial RS232, RS485 and RS422 converters, USB to Serial adapters, Isolators, Ethernet to Serial converters, Serial Repeaters, Wireless Serial modules, Serial Bluetooth adapters and Serial Port Cards.

TECHNICAL SUPPORT

To access technical support, please visit www.NordField.com where you will find:

- Latest drivers and updates
- Technical tips
- Documentation
- Configuration support
- and much more...
- Feel free to contact our technical support team at:
- mail@usconverters.com





105 Stations West Drive Sedona, AZ 86336, USA www.NordField.com mail@NordField.com




DB9 Female (PC)	RS232
1	DCD
2	TXD
3	RXD
4	DTR
5	GND
6	DSR
7	CTS
8	RTS
9	

DB9 Male (Device)	RS232
1	DCD
2	RXD
3	TXD
4	DTR
5	GND
6	DSR
7	RTS
8	CTS
9	






Isolation between two master (DTE) devices.



Isolation between a master (DTE) and a client (DCE) device.



In cases where only the TX line from the isolator is needed for your application -6VDC can be applied to the RX wire (pin 2) and +6V to the GND wire (pin 5) on the isolator. This simulates power provided from a TX line and will provide power to generate a signal on the TX wire from the isolator.

NORDFIELD

Specialists in Serial Communication. With over 15 years of experience in the field we can solve most serial problems.

PRODUCTS

Large selection of Serial RS232, RS485 and RS422 converters, USB to Serial adapters, Isolators, Ethernet to Serial converters, Serial Repeaters, Wireless Serial modules, Serial Bluetooth adapters and Serial Port Cards.

TECHNICAL SUPPORT

To access technical support, please visit www.NordField.com where you will find:

- Latest drivers and updates
- Technical tips
- Documentation
- Configuration support
- and much more...

Feel free to contact our technical

support team at:

mail@usconverters.com

NordField

ELECTRONICS

105 Stations West Drive Sedona, AZ 86336, USA www.NordField.com mail@NordField.com